

Technische Daten/technical data			
Symbol	Soll Reference	Toleranz Tolerance	Dimension
$f_e$	4	$\pm 0.2$	MHz
$B_{-6}$	48	$\pm 10$	%
F	12	$\pm 2$	mm
$FB_6$	2,5	$\pm 0,5$	mm
$FL_6$	7,0	$\pm 1,4$	mm
$D_o$	6 x 20	-0,1	mm x mm
$\beta$	0		Grad/degree
$M_z$	6		mm
P	100		N
$T_a$	-20... +60		°C
$T_{5sec}$	120		°C
$S_{rel}$	-48	$\pm 3$	dB
$C_a$	>50		dB
$e_0$	3	$\pm 1,5$	mm
$e_{20}$	5	$\pm 2,5$	mm
$r_0$	2,5	$\pm 1,3$	mm
$r_{20}$	3,5	$\pm 1,8$	mm
Schwingermaterial/transducer material	Piezokeramik		
Gewicht/weight:	190 g		
Anschluss/connector:	LEMO 00		



www.ilogsa.com

**Prüfkopf-Datenblatt / Probe data sheet**

**SEB 4 (E) No. 57469 + SEKG 2**

Gültig für Prüfköpfe ab: SN 50000  
Valid for probes from: SN 50000  
Id.-No. 28856\_002/05.2008

