

Technische Daten/technical data			
Symbol	Soll Reference	Toleranz Tolerance	Dimension
f_B	4	$\pm 0,2$	MHz
B_{-6}	42,5	$\pm 12,5$	%
F	10	± 1	mm
FB_6	2,1	$\pm 0,4$	mm
FL_6	2	$\pm 0,4$	mm
D_O	$3,5 \times 10$	-0,1	mm x mm
β	60	± 2	Grad/degree
$\Delta B/\Delta T$	0,7	$\pm 0,1$	Grad/degree/10 °C
Z_A	10	± 1	mm
M_z	2		mm
P	100		N
T_a	-20... +60		°C
T_{SSec}	120		°C
S_{rel}	-50	± 3	dB
C_a	>40		dB
s	5	$\pm 2,5$	mm
e_0	3	$\pm 1,5$	mm
e_{20}	6	± 3	mm
r_0	2	± 1	mm
r_{20}	4	± 2	mm
Schwingermaterial/transducer material			Piezokeramik
Gewicht/weight:			32 g
Anschluss/connector:			Microdot

DATENBLATT/DATA SHEET

VS 60 No. 57661 + SEKM 2

Gültig für Prüfköpfe ab: SN 00501
Valid for probes from: SN 00501
Id.-No. 28887 001/09.2005

